



Revision Number: 006.0

Issue date: 04/18/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: TECHNOMELT COOL 250A formerly COOL-LOK 34-250A
Product type/use: Hotmelt adhesive
Restriction of Use: None identified
Company address: Henkel Canada Corporation
 Meadow pine Boulevard 2515
 Mississauga, Ontario L5N 6C3

IDH number: 1389049

Region: Canada

Contact information:
 Telephone: +1 (905) 814-6511
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR FLAMMABLE VAPORS MAY CAUSE IGNITION. VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Wash contaminated clothing before reuse.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 1389049

Product name: TECHNOMELT COOL 250A formerly COOL-LOK 34-250A

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Distillates, petroleum, steam-cracked, polymd.	68131-77-1	5 - 10
Modified rosin ester~		5 - 10

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.
Eye contact:	If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.
Ingestion:	Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Use extinguishing measures appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide.
Special fire fighting procedures:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	No special environmental precautions required. Do not allow material to contaminate ground water system.
Clean-up methods:	Spilled material will solidify. Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling: Always be careful around molten material. Avoid skin contact with molten resins. Follow suggested application temperature. Do not wear contact lenses. At elevated temperatures, irritating fumes may be emitted. Provide adequate ventilation. Wash hands before breaks and immediately after handling the product.

Storage: For safe storage, store between 0.0 °C (32°F) and 38.0 °C (100.4 °F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates, petroleum, steam-cracked, polymd.	None	None	None	None
Modified rosin ester~	None	None	None	None

Engineering controls: Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Respiratory protection: No personal respiratory protective equipment normally required. Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Medium amber
Odor:	Negligible
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	> 200 °C (> 392°F)
Melting point/range:	> 70 °C (> 158°F)
Specific gravity:	0.97
Vapor density:	Not available.
Flash point:	> 200 °C (> 392°F) Cleveland open cup
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not applicable
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	0 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide carbon dioxide
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	To avoid thermal decomposition, do not overheat. Avoid temperatures above 200°C (392°F).

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	Dusts from solid adhesive may cause irritation. Continuous breathing of vapors above molten adhesive may irritate mucous membranes.
Skin contact:	Solid adhesive has no hazards. Molten adhesive may cause severe burns.
Eye contact:	Can cause mechanical irritation if dusts are generated. Fumes released during thermal processing may cause eye irritation. Molten adhesive in eyes will cause severe and permanent damage.
Ingestion:	Not expected under normal conditions of use. Expected to be low in toxicity.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates, petroleum, steam-cracked, polymd.	None	Irritant
Modified rosin ester~	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates, petroleum, steam-cracked, polymd.	No	No	No
Modified rosin ester~	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains, soil or bodies of water.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

Hazardous Materials Information Review Act: ?
?

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/18/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.